

Alloy Steel Fittings - Data Sheet

Mejor Steel, export sourcing for steel pipe and OCTG | Request a quotation: <https://mejorsteel.com/get-a-quote/>

Specifications

Outer diameter	1/2" - 48" (DN15 - DN1200)
Wall thickness	SCH 10 - XXS
Schedule	SCH 10 to XXS, heavy wall available
Length	Center to end per ASME B16.9
Ends	Bevelled to ASME B16.25, or smooth finish
Surface treatment	Black, varnish, or protective coating
Manufacturing process	Seamless, forged and machined, or welded
Pressure rating	Per ASME B16.9 wall thickness and ASME B31.3

Grades supplied

- WP5
- WP9
- WP11
- WP12
- WP22

Inspection & testing

Packaging	Sea-worthy export packing: wooden cases or pallets, tagged with size, grade and heat number; corrosion protection on request.
MOQ	By piece - mixed sizes accepted; no minimum on standard items.
Lead time	Stock items: 5-10 days. Made to order: 3-5 weeks after order confirmation.

- PMI to verify chrome and moly content
- Dimensional inspection per ASME B16.9
- Radiographic or ultrasonic examination
- Hardness testing
- Charpy impact testing

Page: <https://mejorsteel.com/pipe-fittings/alloy-steel-fittings/> | Everything in this data sheet is taken from the published page. The governing standard, MOQ, lead time and price are confirmed on request.