

ASTM A335 Alloy Steel Pipe - Data Sheet

Mejor Steel, export sourcing for steel pipe and OCTG | Request a quotation: <https://mejorsteel.com/get-a-quote/>

Specifications

Outer diameter	1/8" - 36"
Wall thickness	SCH 10 - SCH XXS
Length	SRL, DRL, 20 FT, 40 FT, or custom
Ends	Plain, beveled, threaded
Surface treatment	Black painting, varnish
Manufacturing process	Hot finished seamless, cold drawn seamless
Pressure rating	High temperature and high pressure service

Grades supplied and minimum properties

Grade	Yield strength	Tensile strength
P11	205 MPa min (30,000 psi)	415 MPa min (60,000 psi)
P22	205 MPa min (30,000 psi)	415 MPa min (60,000 psi)
P91	415 MPa min (60,000 psi)	585 MPa min (85,000 psi)

- P1
- P2
- P5
- P9
- P11

Inspection & testing

Packaging	Sea-worthy export packing: bundled by size, plastic caps on both ends, corrosion protection on request, stencilled with size, grade and heat number.
MOQ	One bundle or one truckload; mixed sizes within a bundle accepted.
Lead time	Stock sizes: 7-15 days. Mill run / non-stock: 4-6 weeks after order confirmation.

- 100% ultrasonic testing
- Hydrostatic pressure test
- Tensile, yield and elongation testing
- Hardness testing across the wall
- Chemical analysis including chromium and molybdenum

Page: <https://mejorsteel.com/steel-pipe/astm-a335-alloy-steel-pipe/> | Everything in this data sheet is taken from the published page. The governing standard, MOQ, lead time and price are confirmed on request.