

Casing Centralizer - Data Sheet

Mejor Steel, export sourcing for steel pipe and OCTG | Request a quotation: <https://mejorsteel.com/get-a-quote/>

Specifications

Outer diameter	For 4-1/2" - 20" casing
Wall thickness	Steel thickness 3 - 8 mm
Size range	4-1/2" to 20" casing
Length	Bow spring 200 - 400 mm, rigid 150 - 300 mm
Ends	Hinged, slip-on, or integral
Surface treatment	Painted, galvanized, or bare
Manufacturing process	Stamped and formed steel, welded or hinged
Connection type	Stop collar or integral

Standards, inspection and delivery

Item	Detail
Standard	API Spec 10D, API 5CT
Inspection	Dimensional inspection; Restoring force test; Weld quality inspection; Material certification; Third-party inspection on request
Documents	Mill test certificate to EN 10204 3.1 with the heat number, chemical analysis and mechanical results; EN 10204 3.2 on request. Packing list travels with the shipment.
Packing	Cartons or sacks on pallets
MOQ	100 pieces depending on size
Lead time	15 - 30 days
Supply	Sourced through partner mills; the producing mill is named on the quotation.

Page: <https://mejorsteel.com/casing-tubing/casing-centralizer/> | Everything in this data sheet is taken from the published page. The governing standard, MOQ, lead time and price are confirmed on request.