

Polished Rod Clamp - Data Sheet

Mejor Steel, export sourcing for steel pipe and OCTG | Request a quotation: <https://mejorsteel.com/get-a-quote/>

Specifications

Outer diameter	For 3/4" - 1-1/2" polished rods
Length	Per clamp type and rod size
Ends	Bolted clamp with hardened slips
Surface treatment	Painted or zinc coated
Manufacturing process	Forged and machined, slips hardened
Connection type	Bolted clamp, single or double bolt

Grades supplied

Grade	Minimum tensile strength	Where it is chosen
K	586 MPa (85,000 psi)	Corrosive produced fluids, where cyclic stress and corrosion act together
C	620 MPa (90,000 psi)	Moderate loads - the middle step between K and D
D	793 MPa (115,000 psi)	High rod loads: deeper wells, larger pumps, heavier or more viscous fluid
KD	Sour service grade	Where wet H2S is present and NACE MR0175 applies

Standards, inspection and delivery

Item	Detail
Standard	API 11B, API 11BR, ASTM A29
Inspection	Dimensional inspection; Slip hardness testing; Load and proof testing; Material certification; Visual and magnetic particle inspection
Documents	Mill test certificate to EN 10204 3.1 with the heat number, chemical analysis and mechanical results; EN 10204 3.2 on request. Packing list travels with the shipment.
Packing	Cartons or wooden cases on pallets
MOQ	50 sets depending on size
Lead time	15 - 30 days depending on size
Supply	Sourced through partner mills; the producing mill is named on the quotation.

Page: <https://mejorsteel.com/sucker-rods/polished-rod-clamp/> | Everything in this data sheet is taken from the published page. The governing standard, MOQ, lead time and price are confirmed on request.