

Stainless Steel Pipe - Data Sheet

Mejor Steel, export sourcing for steel pipe and OCTG | Request a quotation: <https://mejorsteel.com/get-a-quote/>

Specifications

Outer diameter	1/8" - 24" (10.3 - 610 mm)
Wall thickness	SCH 5S - SCH 80S, or by wall thickness
Schedule	SCH 5S, 10S, 40S, 80S (ASME B36.19M)
Length	SRL 5.8 m, DRL 11.8 m, or fixed length
Ends	Plain end, beveled end, threaded
Surface treatment	Pickled, annealed and pickled, bright annealed, polished, shot blasted
Manufacturing process	Seamless, ERW welded, EFW welded
Pressure rating	Corrosive and high purity service

Inspection & testing

Packaging	Sea-worthy export packing: bundled by size, plastic caps on both ends, corrosion protection on request, stencilled with size, grade and heat number.
MOQ	One bundle or one truckload; mixed sizes within a bundle accepted.
Lead time	Stock sizes: 7-15 days. Mill run / non-stock: 4-6 weeks after order confirmation.

- Eddy current testing
- Hydrostatic pressure test
- Intergranular corrosion test (ASTM A262) where specified
- PMI positive material identification
- Third-party inspection (SGS, BV, TUV)

Page: <https://mejorsteel.com/steel-pipe/stainless-steel-pipe/> | Everything in this data sheet is taken from the published page. The governing standard, MOQ, lead time and price are confirmed on request.