

Casing, Tubing & Drill Pipe Thread Protectors - Data Sheet

Mejor Steel, export sourcing for steel pipe and OCTG | Request a quotation: <https://mejorsteel.com/get-a-quote/>

Specifications

Outer diameter	For 1.05" - 20" pipe
Wall thickness	2 - 6 mm depending on material
Length	80 - 300 mm depending on pipe size
Ends	Pin protector (for box end), box protector (for pin end)
Surface treatment	Natural, colored, or UV stabilized
Manufacturing process	Injection molded, or steel fabricated
Connection type	Threaded, snap-on, or push-fit

What to state on the enquiry

- The connection: casing, tubing, line pipe or drill pipe, and the thread form, whether STC, LTC, BTC or a named premium connection.
- The end it goes on. Pin and box take different protectors, and the pair is normally quoted together.
- The pipe size, and on larger sizes the coupling outside diameter as well, because the protector is matched to the coupling as much as to the thread.
- The conditions between the mill and the well: months in storage, coastal humidity, direct UV, and whether the pipe is stacked or racked.
- How the pipe is handled on site, since repeated lifting changes the duty class rather than the fit.

Standards, inspection and delivery

Item	Detail
Standard	API 5CT, API 5B, API RP 5A5
Inspection	Dimensional and fit inspection; Material certification; Impact resistance test; Visual inspection
Documents	Mill test certificate to EN 10204 3.1 with the heat number, chemical analysis and mechanical results; EN 10204 3.2 on request. Packing list travels with the shipment.
Packing	Cartons or sacks on pallets
MOQ	500 pieces depending on size
Lead time	15 - 25 days
Supply	Sourced through partner mills; the producing mill is named on the quotation.

Page: <https://mejorsteel.com/casing-tubing/thread-protector/> | Everything in this data sheet is taken from the published page. The governing standard, MOQ, lead time and price are confirmed on request.